

PVS-100 (208 V)
 PVS-100 (240 V)
 PVS-100 (480 V)
 PVS-100 (600 V)
 AE-100 (400V)

Unparalleled Performance

With their advanced system intelligence, next-generation Edge™ MPPT technology, and industrial-grade engineering, PowerGate Plus inverters maximize system uptime and power production, even in cloudy conditions.

Power Efficiency

Power Level	Output Power ¹	Efficiency ²
10%	10 kW	93.2%
20%	20 kW	96.1%
30%	30 kW	96.5%
50%	50 kW	96.7%
75%	75 kW	96.5%
100%	100 kW	96.1%

¹ 315V minimum ² 480V model

Edge MPPT

Provides rapid and accurate control that boosts PV plant kilowatt yield

Provides a wide range of operation across all photovoltaic cell technologies

Printed Circuit Board Durability

Wide thermal operating range: -40° C (-40° F) to 85° C (185° F)

Conformal coated to withstand extreme humidity and air-pollution levels

Proven Reliability

Rugged and reliable, PowerGate Plus PV inverters are engineered from the ground up to meet the demands of large-scale installations.

Low Maintenance

Modular components make service efficient

Safety

UBC Seismic Zone 4 compliant

Built-in DC and AC disconnect switches

Integrated DC two-pole disconnect switch isolates the inverter (with the exception of the GFDI circuit) from the photovoltaic power system to allow inspection and maintenance

PV Inverters | PowerGate[®] Plus 100 kW



PowerGate Plus 100 kW Specifications			UL/CSA	CE
Input Parameters				
Maximum Array Input Voltage	600 VDC		•	
	900 VDC			•
	PV Array Configuration			
Positive Ground		○	○	
Negative Ground		•	○	
Floating			•	
Input Voltage Range (MPPT; Full Power)	315–600 VDC		•	
	420–850 VDC			•
Maximum Input Current	331 ADC		•	
	248 ADC			•
Output Parameters				
Output Voltage Range (L-L)	183–229 VAC	208 VAC	•	
	211–264 VAC	240 VAC	•	
	352–440 VAC	400 VAC		•
	422–528 VAC	480 VAC	•	
	528–660 VAC	600 VAC	•	
Nominal Output Voltage	208 VAC		•	
	240 VAC		•	
	400 VAC			•
	480 VAC		•	
	600 VAC		•	
Output Frequency Range	59.3–60.5 Hz		•	
	49.3–50.5 Hz			•
AC Voltage Range (Standard)	-12%/+10%		•	•
Nominal Output Frequency	60 Hz		•	
	50 Hz			•
Number of Phases	3		•	•
Maximum Output Current per Phase	278 A	208 VAC	•	
	241 A	240 VAC	•	
	145 A	400 VAC		•
	121 A	480 VAC	•	
	96 A	600 VAC	•	
CEC-Weighted Efficiency	96%		•	•
Maximum Continuous Output Power	100 kW (100 kVA)		•	•



Built-in isolation transformer
Protective covers over exposed power connections

Output Options

PowerGate Plus 100 kW

UL/CSA	208 VAC Output
	240 VAC Output
	480 VAC Output
	600 VAC Output
CE	400 VAC Output

Streamlined Design

With all components encased in a single, space-saving enclosure, PowerGate Plus PV inverters are easy to install, operate, and maintain.

Single Cabinet with Small Footprint

Convenient access to all components
Large in-floor cable glands make access to DC and AC cables easy

Rugged Construction

Engineered for outdoor environments

Output Transformer

Provides galvanic isolation

Matches the output voltage of the PV inverter to the grid

©2010 Satcon Technology Corporation. All rights reserved. Satcon, Satcon S-Type, and PV View are registered trademarks, and Edge is a trademark, of Satcon Technology Corporation.

Satcon Corporate
27 Drydock Avenue
Boston, MA 02210
P: 617.897.2400
F: 617.897.2401
E: sales@satcon.com

Satcon West
2925 Bayview Drive
Fremont, CA 94538
P: 510.226.3800
F: 510.226.3801
E: sales@satcon.com

Satcon Canada
835 Harrington Court
Burlington, ON L7N 3P3
Canada
P: 905.639.4692
F: 905.639.0961
E: sales@satcon.com

Satcon Greece
Athanasiou Diakou 2 &
Marathonas Ave
Gerakas 15344
Greece
P: 30 210 6654424
F: 30 210 6654425
E: sales@satcon.com

Satcon Czech Republic
Classic 7 Business Park
Jankovcova 1037/49
170 00 Praha 7
Czech Republic
P: 420 255 729 610
F: 420 255 729 611
E: sales@satcon.com

Satcon Shenzhen China
Room 1112, 11/F, International
Chamber of Commerce,
No. 168 FuHua San Road,
FuTian District, Shenzhen, P.R.C.
518048
P: +86 755 61682588
F: +86 755 61682599
E: sales@satcon.com

Satcon Shanghai China
Room 2308, 23/F, New
HongQiao Center Building,
No. 83 LouGuanShan Road,
Changning District,
Shanghai, P.R.C.
P: 139.1811.2818
E: sales@satcon.com

PowerGate Plus 100 kW Specifications		UL/CSA	CE
Tare Losses	62.3 W	208 VAC	•
	61.6 W	240 VAC	•
	64.5 W	400 VAC	•
	66.1 W	480 VAC	•
	68.0 W	600 VAC	•
Power Factor at Full Load	>0.99	•	•
Harmonic Distortion	<3% THD	•	•
Temperature			
Operating Ambient Temperature Range (Full Power)	-20° C to +50° C	•	•
Storage Temperature Range	-30° C to +70° C	•	•
Cooling	Forced Air	•	•
Noise			
Noise Level	<65 dB(A)	•	•
Combiner			
Number of Inputs and Fuse Rating (2 fuses/input for floating)	5 (110 ADC)	○	
	6 (100 ADC)	○	
	5 (125 ADC)		○
Inverter Cabinet			
Enclosure Rating	NEMA 3R	•	
	IP54		•
Enclosure Finish (14-Gauge, Powder-Coated G90 Steel)	RAL-7032	•	•
Cabinet Dimensions (Height x Width x Depth)	80" x 57" x 30.84" (203.2 cm x 144.78 cm x 78.33 cm)		
Cabinet Weight	2,350 lbs.	1,066 kg	
Transformer			
Integrated Internal Transformer		•	•
Low Tap Voltage ¹	20%	•	•
Testing and Certification			
UL1741, CSA 107.1-01, IEEE 1547, IEEE C62.41.2, IEEE C62.45, IEEE C37.90.1, IEEE C37.90.2		•	
CE Certification (EN 50178, EN 61000-6-2, EN 61000-6-4)			•
UBC Zone 4 Seismic Rating		•	•
Warranty			
Five Years		•	•
Extended Warranty (up to 10, 15, or 20 years)		○	○
Extended Service Agreement		○	○
Intelligent Monitoring			
Satcon PV View® Plus		○	○
Satcon PV Zone		○	○
Third-Party Compatibility		•	•

- Standard
- Optional

¹ The 20% boost tap on the isolation transformer increases the AC voltage output range for applications where the solar array DC operating voltage is at or near the lower end of the DC input range. This boost allows for continued inverter operation at lower DC voltage input levels.

Note: Specifications are subject to change.